

Crossville Studios

STONEFIRE



ALMOND

With a unique shade variation, Stonefire draws its inspiration from the setting sun giving way to shadows. The striations on the tile reflect windswept markings on stone, creating an amazing visual effect that greatly enhances both interiors and exteriors.



ALMOND
ESQSTFALM



NOCE
ESQSTFNOC




BEIGE
ESQSTFBEI



GREY
ESQSTFGRY

Available Sizes

Thickness 10mm



18 x 18



12 x 24




12 x 12



6 x 6



3 x 12
Bullnose



2 x 2 Mosaic
12 x 12 Sheet

Technical Specifications

Product Performance	Result	Testing Method
Water Absorption	≤ 0.5%	ASTM C373
Breaking Strength	≥ 400 lbf	ASTM C648
Freeze Resistance	Resistant	ASTM C1026
Chemical Resistance	Class A	ASTM C650
Stain Resistance	Class A	ASTM C1378
Surface Abrasion	Class IV	ASTM C1027
Scratch Hardness	≥ 6	Mohs Scale
DCOF	≥ 0.42	ANSI A 137.1
Shade Variation	V3	
Grout Thickness	Minimum of 5 mm (3/16") recommended	
Usage	Suitable for residential and commercial interior applications. Not recommended for exterior horizontal applications or in areas where standing water is a common occurrence.	

View other great product options and find detailed product specifications at crossvillestudios.com



Photo features Stonefire Grey 18 x 18.